



Deep Cycle/Industrial Battery Applications

Model	Volts	Ah		RC 25A	RC 75A	Dimensions (in.)			Terminals Available	Weight (lb.)		# of Plates	Cover/Case Color	Pallet Quantity	
		20 Hr.	CCA			L	W	H		Wet	Dry				
Aircraft															
UAC25	12	35	235	35	-	7.71	5.18	7.53	T	26	-	54	Red/Gray	84	
UAC35	12	42	330	45	-	9.78	5.17	7.23	T	35	-	78	Red/Gray	84	
Floor Machine (Sweeper, Scrubber)															
U2500	6	250	-	540	150	11.62	7.12	11.63	S,L	72	59	63	Black/Black	36	
U2500HC	6	275	-	600	168	11.62	7.12	11.63	S,L	78	61	69	Navy/Navy	36	
U3050	6	305	-	675	175	11.88	7.12	15.00	S,L	87	71	57	Black/Black	18	
U3050HC	6	335	-	747	203	11.88	7.12	15.00	S,L	96	78	63	Navy/Navy	18	
UL16	6	375	-	810	214	11.88	7.12	17.00	L,S	111	89	51	Black/Black	18	
UL16HC	6	415	-	890	236	11.88	7.12	17.00	L,S	117	95	57	Navy/Navy	18	
U1450	12	145	-	270	72	13.62	6.75	12.25	L,A	87	71	78	Black/Black	36	
U1850	12	195	-	375	100	15.50	7.06	14.25	S,L	111	90	66	Black/Black	14	
U1850HC	12	215	-	418	110	15.50	7.06	14.25	S,L	116	96	78	Navy/Navy	14	
Golf Car															
JAGC2	6	220	-	492	-	10.38	7.13	11.19	L	66	-	-	Gray/Gray	48	
U2000	6	210	-	420	108	10.25	7.12	11.12	U,S	59	48	45	Black/Black	48	
U2200	6	225	-	447	115	10.25	7.12	11.12	U,S	63	51	57	Gray/White	48	
U2300	6	235	-	448	132	10.25	7.12	11.12	U,S	67	55	63	Green/White	48	
U2400	6	244	-	530	145	10.25	7.12	11.88	U,S	70	60	57	Blue/White	48	
U8VGC	8	165	-	318	85	10.25	7.12	11.33	U,S	65	53	60	Red/White	48	
Marine															
USRM8V19	8	142	600	305	92	19.25	7.50	10.75	L	93	76	100	Rubber (Black)	24	
USRM8V21	8	155	715	330	98	21.44	7.50	10.50	L	103	84	108	Rubber (Black)	24	
USRM8V24	8	190	880	430	134	24.38	7.44	10.50	L	118	96	132	Rubber (Black)	16	
USRM8V27	8	215	1000	445	122	27.44	7.44	10.50	L	132	108	148	Rubber (Black)	16	
USRM8V26	8	240	1050	515	145	26.75	8.44	11.12	L	149	121	156	Rubber (Black)	16	
Multi-Purpose Deep Cycle															
USRM1	6	95	-	165	44	9.13	7.13	9.38	S,A	30	24	45	Black/Black	72	
USRMU1	12	35	-	55	15	8.19	5.19	7.12	L	21	18	60	Red/White	120	
USRM22NF	12	60	-	108	31	9.44	5.50	9.00	S,A	34	28	66	Red/White	84	
USRM22F	12	65	-	98	24	9.50	6.56	8.31	S	35	29	66	Black/White	72	
USRM78	12	70	-	122	34	10.25	7.06	8.00	I	43	35	78	Black/Black	72	
UBIGJOE	12	107	-	185	48	18.00	7.25	9.63	A,S	80	65	102	Rubber (Black)	28	
USRM16TF	12	120	-	250	74	16.56	7.12	11.12	S,A	91	74	66	Rubber (Black)	28	
USRM8D	12	240	-	455	106	20.75	11.12	9.88	S,A,L	127	104	174	Black/Black	16	

Model	Volts	Ah 20 Hr.	CCA	RC 25A	RC 75A	Dimensions (in.)			Terminals Available	Weight (lb.)			# of Plates	Cover/Case Color	Pallet Quantity
						L	W	H		Wet	Dry				
Starting															
U17HF-50	6	-	360	115	-	7.38	6.88	9.25	A	26	21	39	Rubber (Black)	90	
U19L-50	6	-	525	110	-	8.19	6.69	7.44	A	26	21	39	Rubber (Black)	90	
U2E-VHD	6	-	600	180	-	19.38	4.12	9.12	A	38	31	45	Rubber (Black)	60	
U2N-VHD	6	-	625	200	-	10.00	5.56	9.00	A	36	29	51	Rubber (Black)	84	
U2-XHD	6	-	675	185	-	10.38	7.12	9.38	A	35	29	51	Black/Black	72	
U4-RD	6	-	860	240	-	13.13	7.13	9.38	A	44	36	63	Black/Black	54	
U3EH-VHD	6	-	875	300	-	19.31	4.19	9.81	A	47	38	69	Black/Black	60	
U4-XHD	6	-	1000	320	-	13.13	7.13	9.38	A	50	41	75	Black/Black	54	
U4EH-VHD	6	-	1000	325	-	19.31	5.00	9.81	A	61	50	81	Rubber (Black)	48	
U1-8V-VHD	8	-	400	140	-	8.88	6.81	8.50	A	38	31	52	Rubber (Black)	72	
U2-8V-VHD	8	-	500	140	-	10.38	6.94	9.06	A	44	36	60	Rubber (Black)	72	
U911-50	12	-	300	65	-	8.19	6.88	6.88	A	28	23	54	Red/White	90	
U53K-VHD	12	-	360	80	-	12.75	4.62	8.94	A	35	29	54	Rubber (Black)	90	
U26-VHD	12	-	450	65	-	8.19	6.81	8.00	S,U	28	23	54	Black/Black	90	
U3EE-VHD	12	-	450	100	-	19.31	4.19	8.88	A	40	33	60	Black/Black	60	
U3ET-VHD	12	-	500	140	-	19.31	4.38	9.88	A	50	41	66	Black/Black	60	
U27-50	12	-	525	120	-	12.06	6.81	8.88	A	46	37	78	Black/Black	54	
U60K-VHD	12	-	550	126	-	13.06	6.19	8.88	A	50	41	66	Rubber (Black)	54	
U17TF-VHD	12	-	625	150	-	17.06	6.94	8.00	A	61	50	102	Rubber (Black)	42	
U6TL	12	-	825	215	-	11.88	10.50	11.88	A	69	56	138	Olive/Olive	32	
U8D-1075	12	-	1100	290	-	20.75	11.12	9.88	B,C,L	112	92	138	Black/Black	16	
U8D-1400	12	-	1450	400	-	20.75	11.12	9.88	B,C,L	129	105	186	Black/Black	16	
U16V24	16	-	550	70	-	10.08	6.38	8.79	A	42	-	72	Red/Red	-	
U16V324	16	-	550	70	-	10.08	6.38	8.79	A	42	-	72	Red/Red	-	
U4HN	24	-	235	28	-	10.25	5.25	9.00	A	-	28	-	Black/Black	-	

Notes:

"Weight, Dry": A dry battery ships without electrolyte. Most are actually "hibernated" (moist). Dry batteries are available only with standard terminals.

"Speed Caps" are standard equipment on Golf Car batteries. (UAGC2 is a sealed battery and has no caps.)

Terminals: For each battery, standard terminal is listed first.

Code	Terminal Description	Fractions and Decimal Equivalents			
		1/16	0.06	9/16	0.56
A	Auto Post	1/8	0.12	5/8	0.62
B	Bus (3/8" threaded studs)	3/16	0.19	11/16	0.69
C	Bus (1/2" pos. stud, 3/8" neg. stud)	1/4	0.25	3/4	0.75
I	Threaded side insert-tube	5/16	0.31	13/16	0.81
L	L-shaped bracket with hole	3/8	0.38	7/8	0.88
S	Auto post with horizontal hole	7/16	0.44	15/16	0.94
T	Threaded stud	1/2	0.50		
U	Threaded stud over auto post				